



# Product Datasheet

## D347-V – Double-Coated Tissue Tape

### Description:

A product that is great for general purpose bonding, fixing, mounting, and splicing. It is hand-tearable with high tack and quick bond. This is a great laminating adhesive with a solvent acrylic adhesive system.

➡ Excellent for foam laminating and mounting nameplates and signs.

### Features:

- High tack and quick bond
- Good laminating adhesive
- Shears cleanly on plastic
- Hand-Tearable



### Product Data

Carrier Type	Tissue	0.59 mil	.015 mm
Adhesive Type	Acrylic Solvent	-	-
Adhesive Thickness	-	3.2 mil	.082 mm
Liner Thickness	-	3.9 mil	.100 mm
Total Tape Thickness	-	7.2 mil	.184 mm
Peel Adhesion	From Stainless Steel	53 oz/in	15N/25mm
Temperature Resistance	-	212° F	100° C
Color	Transparent		

Assembly

Bonding

Masking

Splicing

### Application Notes:

General purpose bonding and binding tape. Can be used for foam gasketing and sound attenuation.

To achieve ultimate adhesion, the bonding surface should be dry, clean, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.